PURCHASE ORDER

QR-ADMPPS-04

INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

DOST Compound, Gen. Santos Ave., Bicutan, Taguig City DOST Trunkline: 837-2071 local 2220 / 2221 15-4477

Address: Sta MB Aguirre Bidg III. F. Rayes St. Balbbago. Sta. Rosa, Laguna	. , ,	·	1	DOST Trunkline: 837-2071 local 2220 / 222				
Sa MB Aguire Blog III, F. Roys St. Ballobago, Sta Rosa, Laguna Resolution No. PR # 11-2015-0335 ASC # 535-2015	GIA-E-382-2015			P.O. No.:	ELLAB PHILS. CORP.		Supplier:	
Balibago. Sta. Rosa, Laguna Resolution No. PR # 11-2015-0336 ASC # 535-2015		2015	December 14,	Date:	uirro Blda III. E. Boyon St	58 MB Aau	Address:	
Resolution No. PR # 11-2015-0336 ASC # 535-2015		J	Public Bidding	Mode of Procurement:				
Centlemen: Please furnish this office the following articles to the terms and conditions contained herein: Please of Delivery: Date of Delivery: Metrology Bidg. (not later than 3:00 P.M.) Delivery Term: Please of Delivery: Date of Delivery: Stock No. Unit Set Thermal Validation and Monitoring System Master module with minimum 16 channel/inputs with data handling system enclosed in a heavy duty, hard carrying case 1) Temp. Range measured: at least -200°C - 4400°C 2) Accommodates thermocouple probes type T or K sensors 3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) 5) With certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)) Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HOT) with traceable calibration certificate Accessories: 9) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Very Truly yours. Conforme: (Signature over printed name) (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available:	/			Possiution No.		_		
Please furnish this office the following articles to the terms and conditions contained herein: Please for Delivery: Metrology Bidg. (not later than 3:00 P.M.) Delivery Term: Sixty (60) calendar of Delivery: Payment Term: Stock No. Unit Description Quantity Unit Cost Am		535-2015	ASC #				PO-08-9	
Place of Delivery: Stock No. Unit Description Quantity Unit Cost Am Thermal Validation and Monitoring System Master module with minimum 16 channel/inputs with date handling system enclosed in a heavy duty, hard carrying case 1) Temp. Range measured: at least -200°C - +400°C 2) Accommodates thermocouple probes type T or K sensors 3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) Silvith certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) Process Adequacy Measurements with traceable celibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Mount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours. Conforme: (Signature over printed name) (Signature over printed name) (Signature over printed name)		000-2010	7,00 #			7		
Stock No. Unit Description Payment Term:			· · · · · · · · · · · · · · · · · · ·			rnish this o	Please f	
Stock No. Unit Description Quantity Unit Cost Am Thermal Validation and Monitoring System Master module with minimum 16 channel/inputs with data handling system enclosed in a heavy duty, hard carrying case 1) Temp. Range measured: at least -200°C - +400°C 2) Accommodates thermocouple probes type T or K sensors 3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) Silvith certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours. Conforme: (Signature over printed name) (Signature over printed name) (Signature over printed name)	alendar days	Sixty (60) cale		r than 3:00 P.M.)	Metrology Bidg. (not later	-		
1 set Thermal Validation and Monitoring System Master module with minimum 16 channel/inputs with data handling system enclosed in a heavy duty, hard carrying case 1) Temp. Range measured: at least -200°C - +400°C 2) Accommodates thermocouple probes type T or K sensors 3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) 5) With certificate of compliance to FDA 21 CFR Part II: GAMPS-Approved 6) Can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Poetration Studies (HPT)/Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Poetration Studies (HPT)/Process Adequacy Measurements with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours. Conforms: (Signature over printed name) (Signature over printed name) (Date) Funds Available: Amount		Unit Cont	· · · · · · · · · · · · · · · · · · ·	Description				
Master module with minimum 16 channel/inputs with data handling system enclosed in a heavy duty, hard carrying case 1) Temp. Range measured: at least -200°C - 440°C 2) Accommodates thermocouple probes type T or K sensors 3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) 5)With certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Poetration Studies (HPTI/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Destration Studies (HPTI/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words)	Amount	Onit Cost	Quantity					
handling system enclosed in a heavy duty, hard carrying case 1) Temp. Range measured: at least -200°C - +400°C 2) Accommodates thermocouple probes type T or K sensors 3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) 5) With certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Cate) Funds Available: Funds Available: Amount	4,947,660.1		3	d Monitoring System	Thermal Validation an	set	1	
1) Temp. Range measured: at least - 200°C - +400°C 2) Accommodates thermocouple probes type T or K sensors 3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) 5) With certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) Can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount				mum 16 channel/inputs with data	Master module with minir			
2) Accommodates thermocouple probes type T or K sensors 3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) 5) With certificate of compliance to FDA 21 CFR Part II: GAMPS-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts [Total Amount in Words] In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme:								
3) With internal rechargeable battery for backup if power failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (90-240 VAC, 60Hz) 5) With certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with sillicone washer) -16 pcs. Papace Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) in case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Cate) Requisitioning Office/Dept. Funds Available: Amount	1000							
failure occurs or electricity is not available for minimum of 2 hours 4) Universal Power (30-240 VAC, 60Hz) 5)With certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours. Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount					1			
4) Universal Power (90-240 VAC, 60Hz) 5) With certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount				failure occurs or electricity is not available for minimum of				
5)With certificate of compliance to FDA 21 CFR Part II: GAMP5-Approved 6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) in case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount				10 VAC, 60Hz)				
6) can be used as a stand-alone or interfaced to a computer 7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount	7.7			pliance to FDA 21 CFR Part II:				
7) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) in case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount					GAMP5-Approved			
at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours. Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount								
Process Adequacy Measurements with traceable calibration certificate 8) minimum 16 pcs. Thermocouples (type T or K sensors) of at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate				at least 7-m cable length for Heat Penetration Studies (HPT)/ Process Adequacy Measurements with traceable calibration				
at least 7-m cable length for Heat Distribution Tests (HDT) with traceable calibration certificate Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount								
Accessories: a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount								
a) For mounting in Containers/Packaging -16 pcs. Packing Glands for Filled Containers (complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount				_			To your market or	
(complete with silicone washer) -16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount				iners/Packaging				
-16 pcs. Space Bars / Spacers b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount								
b) To introduce Temperature and Pressure Sensors inside the processing machineries such as retorts Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount								
the processing machineries such as retorts [Total Amount in Words] In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount								
Page 1 of 2 pages (Total Amount in Words) In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount	•							
(Total Amount in Words) in case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of deshall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount						pages	Page 1 of 2	
Shall be imposed. Very Truly yours, Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount					5)	ınt in Words	(Total Amo	
Conforme: (Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount	day of delay	rcent for every da	enth (1/10) of one pe	he time specified above, a penalty of one-t	make the full delivery within the	of failure to roosed.	In case of shall be imp	
(Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount			ruly yours,	Very				
(Signature over printed name) (Date) Requisitioning Office/Dept. Funds Available: Amount								
(Date) Requisitioning Office/Dept. Funds Available: Amount							Conforme:	
(Date) Requisitioning Office/Dept. Funds Available: Amount								
Requisitioning Office/Dept. Funds Available: Amount					ture over printed name)	(Signa		
			<u> </u>		(Date)			
11.000			Amount		ept. Funds Available:	Requisitioning Office/Dept. Funds Availab		
ALOBS No.			ALOBS No.					
			-					
201	PO form/PPS/n							

/

PURCHASE ORDER

QR-ADMPPS-04

INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

Supplier:	ELLAB P	HILS. CORP.	P.O. No.:	GIA-E-38	2-2015	
Address:			Date:			
. 144. 555.	5B MB Aguirre Bldg. III, F. Reyes St., Balibago, Sta. Rosa, Laguna		Mode of Procurement:	December 14, Public Bidding		
PO-08-9			Resolution No.	delica es Millo ades		
			PR # 11-2015-0336	ASC#	535-2015	
entlemen: Please fi		ffice the following articles to	the terms and conditions contained here	-		
lace of De	livery:	Metrology Bldg. (not late	r than 3:00 P M)			
ate of Deli			Triali 0.00 F.MI.	Delivery Term: Payment Term:	Sixty (60) cal	endar days
Stock No.	Unit		Description	Quantity	Unit Cost	Amount
		(no holes) 1" -1 pc. Packing outer 1" -1 pc. Rubber packing	with 16 holes, 1" for HPT		/	4,947,660.1
		-1 pc. Feed through 1" -1 pc. Pouch fittings c) inclusive of certificate temperature sensors d) inclusive of training fo e) after sales service: with service and parts and if f) country of origin: Denning) units to be delivered to	h at least 3 years warranty on regular maintenance support	Less: VAT EWT	220,877.68 44,175.54	``
ENDUSEF CHARGE T		DOST 2 FIC, DOST 8 FIC, DOST-HITS Project	AND DOST 11 FIC			
PREPARED	BY:		AN IMA			Management of the state of the
			/ EEL LEE C. DELUTA inistrative Officer V			78
		[
ann a ne		,				
Page 2 of 2 Total Amou	<i>pages</i> int in Words	Four million air b	undred eights too the			
	of failure to m		undred eighty two thousand six hundred ne time specified above, a penalty of one	e-tenth (1/10) of one pe	ercent for every da	ay of delay
Conforme:	(Signat	ure over printed name)	Ver	NOTE YOURS, RICIAV. AZANZA, Ph.I	<u>D.</u>	
		(Date)				
Requisitioni	ng Office/De			Amount		
Pullos Available. Pullos Available. NELIA ELISA C. FLORENDO			SOLEDAD S. REYES	ALOBS No.		
	Chief-TSD		Accountant IV mv			

EVINCEL MANIGEMENT DIVILLE Date /.